



FO1 IT FRAME 19"

Fo1 81220



**FO1 IT FRAME 19"****Fo1 81220**

|              |                  |               |                      |
|--------------|------------------|---------------|----------------------|
| NAMN         | <b>FO1 81220</b> | PRODUKT EAN   | <b>7330701086298</b> |
| ART. NR      | <b>55830</b>     | ETIM          | <b>EC002499</b>      |
| ENUMMER      | <b>2500583</b>   | TULL TARIFKOD | <b>94032080</b>      |
| BREDD        | <b>800 MM</b>    |               |                      |
| DJUP         | <b>1200 MM</b>   |               |                      |
| HÖJD         | <b>2200 MM</b>   |               |                      |
| FÄRG         | <b>BEIGE</b>     |               |                      |
| URSPRUNGLAND | <b>SWEDEN</b>    |               |                      |

**Teknisk information och certifikat**

- Screw-assembled frame with aluminium profiles and die-cast zinc corners. The frame has two integrated vertical screw pockets in each corner profile for universal mounting of accessories.



- Frame can be dismantled by means of screws.
  - Surface treatment: textured Enoc System beige.
  - Ingress protection class IP20.
  - Maximum static load 1,500 kg, and divided on 4 19" profiles
  - Frame has no doors or side panels. Can be supplemented with door and side panels from our range of accessories.
  - Frame without top panels. Can be supplemented with top panels from our range of accessories.
  - The base is open, but can be fitted with cover plate/ base plate packages.
  - The 19" profiles can be steplessly repositioned through the depth of the enclosure. The depth profiles have markings for precise positioning. The 19" profiles are numbered in height units.
- The whole assembly can be moved right or left to an off-centre position.

## Leveransbeskrivning

---

Assembled with 2 19" profiles

Central grounding Point M5 in the corner post.