



S1 SERVER RACK 19"

S1 81020-V





S1 SERVER RACK 19"

S1 81020-V

NAMN	S1 81020-V	PRODUKT EAN	7330701105180
ART. NR	58119	ETIM	EC002499
ENUMMER	2503789	TULL TARIFKOD	94032080
BREDD	800 MM		
DJUP	1000 MM		
HÖJD	2000 MM		
FÄRG	BLACK		
URSPRUNGSLAND	SWEDEN		

Teknisk information och certifikat

- Screw-assembled frame with aluminium profiles and diecast zinc corners. The frame has two integrated vertical screw pockets in each corner profile for universal mounting of accessories.
- Frame can be dismantled by means of screws.
- Finish: textured black RAL 9005 or White RAL 9003.
- Ingress protection class IP20.
- Maximum static load 1.500 kg, divided on 4 19" profiles.
- 1 central earthing point M5 in left rear corner post.
- The 19" profiles can be steplessly repositioned through the depth of the enclosure. The depth profiles have markings for precise positioning and are numbered in height units. The whole assembly can be moved right or left to an off-centre position (800 mm width). Enclosures have two pairs of 19" profiles. One pair is pre-installed at a depth of 100 mm from the front of the enclosure and the other pair is pre-installed 600 mm further in 800 mm depth and 740 mm further in 1000 and 1200 mm depth.

Front door and back door

- Front and rear door is made of 1 mm perforated sheet steel built into an aluminium frame. 85% perforation (hexagonal) on perforated surface area. LS 95 ergonomic locking handle with C101 safety cylinder. Can be adapted for other lock systems. Integrated quick lock system allows door to be removed without use of tools. Door opening angle >180° in single enclosure configuration. Righthinged, possibility to left hanging.

Side panels



- Sheet steel side panels, easy to detach and lockable from inside.

Top panels

- The top consists of replaceable modular panels. Two panels has cable glands with brushstrip on the left and right side rear and the rest are cover plates. Can be replaced with ventilation panels, fan packages or panels with integrated cable glands. All modules can be rotated 90°. The U-shaped panel with integrated cable glands makes it easy to move pre-existing installations into the enclosure.

Bottom

- The base is open, but can be fitted with cover plate/base plate packages.

Leveransbeskrivning

Locking handle LS 95 with safety cylinder C101.

4 keys C101.

4 19" profiles.

Central grounding Point M5 in the corner post.