



NSVE WALL CABINET

NSVE 104-P





## NSVE WALL CABINET

# NSVE 104-P

|              |                   |               |                      |
|--------------|-------------------|---------------|----------------------|
| NAMN         | <b>NSVE 104-P</b> | PRODUKT EAN   | <b>7330701071720</b> |
| ART. NR      | <b>53832</b>      | ETIM          | <b>EC002500</b>      |
| ENUMMER      | <b>2511837</b>    | TULL TARIFKOD | <b>94032080</b>      |
| BREDD        | <b>565 MM</b>     |               |                      |
| DJUP         | <b>465 MM</b>     |               |                      |
| HÖJD         | <b>510 MM</b>     |               |                      |
| FÄRG         | <b>BEIGE</b>      |               |                      |
| URSPRUNGLAND | <b>SWEDEN</b>     |               |                      |

## Teknisk information och certifikat

---

- Made of sheet steel, aluminium profiles and die-cast zinc corner pieces.
- Finish: Enoc System textured beige.
- Glass or metal door. Glass door is made of smoke-coloured safety glass, metal door is made of sheet steel.  
Doors reinforced with aluminium profiles and sheet steel.
- Door opening angle 180°.
- Locking knob LS 15 with standard lock cylinder for key C101.
- Sheet steel side panels, easy to detach, fixed with a screw from the inside.
- The top and bottom have a new larger adjustable cable gland with a foam plastic seal. Knock-out panel can be replaced with ventilation plates (VPE) or fan packages (FPME).
- One pair of 19-inch profiles (482.6 mm) pre-fitted 110 mm in from the enclosure front, can be repositioned at 30 mm intervals through half the depth of the enclosure.
- Extra pair of 19 profiles available as accessory.
- Supplied with cover panel (TPA) installed in the 19-inch profiles. (Does not apply to 6HU.)
- Back/mounting panel (BS NSVE) available as accessory.
- Wall attachment profile for quick wall installation.
- Maximum static load 50 kg.
- Ingress protection class IP 20.