NSVB WALL CABINET

NSVB 6406-P



NSVB WALL CABINET

NSVB 6406-P

NAME	**NSVB 6406-P**	PRODUKT EAN	**7330701000126**
ART.NR	**52012**	ETIM	**EC002500**
EAN	**2595091**	TULL TARIFKOD	**94032080**
BREITE	**600 MM**		
TIEFE	**400 MM**		
HÖHE	**600 MM**		
FARBE	**BEIGE**		
HERKUNFTSLAND	**SWEDEN**		

Technische Informationen

- Made of aluminium profiles and diecast zinc corner pieces.
- Glass or metal door. Glass door is made of smoke-coloured safety glass reinforced with black anodised aluminium profiles, metal door is made of sheet steel.
- Door opening angle 190°.
- Door are standard right-hinged, possible left hanging.
- Locking handle LS 75 with standard lock cylinder for key C101. Can be adapted for other lock systems.
- Sheet steel side panels, easy to detach and lockable from inside. Integrated handle for easier use.
- The top and bottom consist of replaceable modular plates, one with cable glands (KGF) including an adjustable foam plastic seal and rest cover plates (BPT/UP). Can be replaced with ventilation panels (VP) or fan packages (FPM/FPS).
- Back panel not included, available as accessory (BS).
- Two wall attachment profiles for quick wall installation.
- One pair of 19" profiles (482,6 mm), can be steplessly repositioned through the depth of the enclosure. Additional 19" profiles (PR) are available as accessories.
- Enclosure is detachable.
- Maximum static load 80 kg.
- Ingress protection class IP 20.

Lieferumfang

Locking handle LS 75 with saftey cylinder C101.
2 keys C101.
2 19" profiles.
Central grounding Point M5 in the corner post.