

NSVB WALL CABINET

NSVB 6506-P







NSVB WALL CABINET

NSVB 6506-P

NAMNNSVB 6506-P PRODUKT EAN 7330701000324 ART. NR 52032 ETIM EC002500 ENUMMER 2595101 TULL TARIFKOD 94032080 BREDD 600 MM DJUP 500 MM HÖJD 600 MM FÄRG BEIGE URSPRUNGSLAND **SWEDEN**

Teknisk information och certifikat

- Made of aluminium profiles and diecast zinc corner pieces.
- Glass or metal door. Glass door is made of smoke-coloured safety glass reinforced with black anodised aluminium profiles, metal door is made of sheet steel.
- Door opening angle 190°.
- Door are standard right-hinged, possible left hanging.
- Locking handle LS 75 with standard lock cylinder for key C101. Can be adapted for other lock systems.
- Sheet steel side panels, easy to detach and lockable from inside. Integrated handle for easier use.
- The top and bottom consist of replaceable modular plates, one with cable glands (KGF) including an adjustable foam plastic seal and rest cover plates (BPT/UP). Can be replaced with ventilation panels (VP) or fan packages (FPM/FPS).
- Back panel not included, available as accessory (BS).
- Two wall attachment profiles for quick wall installation.
- One pair of 19" profiles (482,6 mm), can be steplessly repositioned through the depth of the enclosure.
 Additional 19" profiles (PR) are available as accessories.
- Enclosure is detachable.
- Maximum static load 80 kg.
- Ingress protection class IP 20.

Leveransbeskrivning





Locking handle LS 75 with saftey cylinder C101. 2 keys C101. 2 19 profiles. Central grounding Point M5 in the corner post.

