



NSVB WANDSCHRANK SCHALLGEDÄMMT

NSVB SR 6606-P



**NSVB WANDSCHRANK SCHALLGEDÄMMT****NSVB SR 6606-P**

NAMN	<b>NSVB SR 6606-P</b>	PRODUKT EAN	<b>7330701038808</b>
ART. NR	<b>57681</b>	TULL TARIFKOD	<b>94032080</b>
ENUMMER	<b>2502055</b>		
BREDD	<b>600 MM</b>		
DJUP	<b>600 MM</b>		
HÖJD	<b>600 MM</b>		
FÄRG	<b>BEIGE</b>		
URSPRUNGLAND	<b>SWEDEN</b>		

**Teknisk information och certifikat****Silence**

NSVB SR is standard Enoc NSVB cabinet built to reduce the emitting noise from any equipment inside the rack.



## Performance

Adding SRM mat to sidepanels, roof, bottom and front door.

### **The noise level will be lowered substantially.**

In testing we have reduced the noise level substantially. Fan with a typical active equipment noise have the following result:

Open frame: 55 dBA (measured from 1 m distance).

NSVB standard: 50 dBA

NSVB SR: 42 dBA\*

\*For reference, "normal" office background noise is around 40 dBA.

- Made of aluminium profiles and diecast zinc corner pieces.
- Metal door from sheet steel.
- Door opening angle 190°.
- Door are standard right-hinged, possible left hanging.
- Locking handle LS 75 with standard lock cylinder for key C101. Can be adapted for other lock systems.
- Sheet steel side panels, easy to detach and lockable from inside. Integrated handle for easier use.
- The top and bottom consist of replaceable modular plates, one with cable glands (KGF) including an adjustable foam plastic seal and rest cover plates (BPT/UP). Can be replaced with ventilation panels (VP) or fan packages (FPM/FPS).
- Back panel not included, available as accessory (BS).
- Two wall attachment profiles for quick wall installation.
- One pair of 19" profiles (482,6 mm), can be steplessly repositioned through the depth of the enclosure. Additional 19" profiles (PR) are available as accessories.
- Enclosure is detachable.
- Maximum static load 80 kg.
- Ingress protection class IP 20.